Technical overview.

EMOTION 300

	Basic data						Microphone system				Signal processing (one step)								Signal transmission/ binaural hearing		Details									Remote control	
	Performance data (2 cc coupler)	Battery size	Number of channels (G/MG/O)	Number of microphones	Number of programs	Connection to the computer	Automatic/Natural Sound	Dir. adaptive	Dir.	Omni	DataLogging	Acclimatisation Manager	Voice Detection	Noise Reduction	Sound Impulse Management	Active Wind Block	Feedback Management	Situation Optimiser	Bluetooth functionality	i-com2	MultiMic	PhoneConnect	Contactmatic	Volume control (VC)	Program pushbutton	Telephone Coil	Audio input/audio adapter FM (voice-activated) Selection: A MA A/MA/M	Child earhook	Battery compartment lock	Media (Bluetooth)	eMote
Mini	124/40	312	8/4	2	3	Prog. socket	•		•	•	•		•	•			•				•										•
Slim	125/58	312	8/4	2	3	Prog. socket	•		•	•	•		•	•			•				•			•	•	•			•		•
Power	136/75	13	8/4	2	4	Prog. socket	•		•	•	•		•	•			•				•			•	•	•	•	•	•		•
CIC	110/30 115/35	10	8/4	1	3	Flex Connect				•	•		•	•			•								•						•
Mini-Canal	115/40 120/45	10	8/4	2	3	Flex Connect	•		•	•	•		•	•			•				•		•	•	•	•					•
Canal	115/45 120/50	312	8/4	2	3	Flex Connect	•		•	•	•		•	•			•				•		•	•	•	•					•
Concha	120/45 125/50	13	8/4	2	3	Flex Connect	•		•	•	•		•	•			•				•		•	•	•	•					•